

# TECHNICAL DATA

# **Scapa 3370**

**Uncoated Rayon Cloth Tape** 

#### DESCRIPTION

Scapa 3370 is an uncoated rayon cloth tape with a pressure sensitive adhesive. Scapa 3370 is available in variety of colours including black, natural and white.

### **APPLICATIONS**

- Designed for the hand application of tape for wrapping cable and wire harness, particularly in the automotive industry.
- General protection of polished surfaces and machined parts against corrosion and damage.
- General purpose applications such as packaging, masking and identification.

### **PRODUCT BENEFITS**

- Rayon cloth base provides excellent strength
- Corrosion resistant
- Abrasion resistant
- Available in a range of colours for identification applications
- Very conformable and flexible
- Easy tear by hand
- Good unwind properties
- Excellent initial tack and ultimate adhesion
- Certain colours can be supplied to DEF STAN 75-2 specification

Issue: 5 Date: 26.06.10 Page 1 of 2 3370.doc

#### www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.

### **TECHNICAL PROPERTIES**

	Unit	Nominal Value	Test Method
Thickness	mm	0.24	AFERA 5006*
Tensile Strength	N/cm	80	IEC 454-2
Adhesion to Steel	N/cm	3.0	IEC 454-2
Service Temperature	°C	-10 - 70	

<sup>\*</sup> Scapa Internal Test Method to measure thickness now replaced by the more rigorous AFERA method

## STANDARD PRESENTATION

Roll Length: 25m, 50m

Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm

Core: Cardboard

Packaging: Scapa branded, bulk packed using interleaving sheets between layers.

Note: Information on stock items, non-standard sizes, and lead times is available on request.

#### RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Surfaces should be clean, dry and free from dusty, grease or other contaminants. Shelf life will vary with conditions of use and is affected by climate environment, but it is recommended that the product should be used within 6 months of date of manufacture, if stored in a moderate climate and good conditions.

ssue: 5 Date: 28.06.10 Page 1 of 2 3370.doc

www.scapa.com